



energising life

MOTOR GASOLINE

BHARAT STAGE III

TEST	METHOD	SPECIFICATION	
		MS 91	MS 95
Grade			
Density @ 15°C, kg/m ³	IS 1448 P :16	720 - 775	720 - 775
Colour, Visual		Orange	Red
Copper Strip Corrosion (3 hrs. @ 50°C)	IS 1448 P :15	Class 1	Class 1
Existent gum, gm/m ³	IS 1448 P :29	Max. 40	Max. 40
Lead Content (as Pb), gm/litre	IP 352	Max. 0.005	Max. 0.005
Research Octane Number (RON)	IS 1448 P :27	Min. 91	Min. 95
Motor Octane Number (MON)	IS 1448 P :26	Min. 81	Min. 85
Reid Vapour Pressure @ 38°C, kPa ⁽¹⁾	IS 1448 P :39	Max. 60	Max. 60
Distillation :	IS 1448 P :18		
Recovery upto 70°C, %v		10-45	10-45
Recovery upto 100°C, %v		40-70	40-70
Recovery upto 150°C, %v		Min. 75	Min. 75
FBP, °C		Max. 210	Max. 210
Residue, %v		Max. 2	Max. 2
Benzene content, % v	ASTM D3606	Max. 1	Max. 1



energising life

Total Sulphur, %wt.	ISO 14596	Max. 0.015	Max. 0.015
Vapour Lock Index (VLI): a) Summer ⁽²⁾	Note (3)	Max. 750	Max. 750
b) Other months (Winter)		Max. 950	Max. 950
Oxidation Stability, minutes	IS 1448 P : 28	Min. 360	Min. 360
Olefin content, %v	IS 1448 P : 23	Max. 21	Max. 18
Aromatics content, %v	IS 1448 P : 23	Max. 42	Max. 42
Oxygen content, %wt.	IS 2796:2008 Annexure C & D	Max. 2.7	Max. 2.7
Oxygenates content, %v	IS 2796:2008 Annexure C		
a) Methanol		Nil	Nil
b) Ethanol		Max. 5	Max. 5
c) Iso-propyl alcohol		Max. 10	Max. 10
d) Iso-butyl alcohol		Max. 10	Max. 10
e) Tertiary-butyl alcohol		Max. 7	Max. 7
f) Ethers containing 5 or more 'C' atoms per molecule		Max. 15	Max. 15
g) Other Oxygenates		Max. 8	Max. 8
TEST	METHOD	SPECIFICATION	
Grade		MS 91	MS 95
Engine intake system cleanliness ⁽⁴⁾	As per IS 2796	Report - MFA used	Report - MFA used



energising life

Water Tolerance of gasoline alcohol blends, temperature for phase separation, °C,			
a) Summer ⁽²⁾		Max. 10	Max. 10
b) Winter (5)		Max. 0	Max. 0

Conforms to BIS spec IS:2796-2008 For Motor Gasoline

- Note :**
- 1) For the gasoline-alcohol blends, the dry vapour test method given in Annex A shall be followed.
 - 2) Summer shall be the period from May to July.
 - 3) $VLI = 10RVP + 7E70$
 - 4) Use of multi-functional additives (MFA) is a requirement for assuring adequate fuel system and intake system cleanliness performance in engines. Refiners/Marketers of motor gasoline have to ensure the MFA has proper credentials from internationally accepted test laboratories/authorities.
 - 5) In winter it is expected that temperature may be lower than 0°C in the northern hilly region and hence phase separation shall not take place till -10°C.